



MILLERS OILS

millersoils.co.uk

PRODUCT DATA SHEET
COMMERCIAL
VEHICLE



DATA SHEET NO: 5386

PRODUCT NAME/VISCOSITIES:

MILLERMATIC ATF UN

DESCRIPTION:

Selected high quality solvent refined base stocks with performance additives.

APPLICATION:

For use in automatic transmission and power steering systems in accordance with the manufacturer's instructions.

USER BENEFITS:

- Type ATF - UN provides a universal lubricant for the majority of automatic transmissions.
- Automotive, industrial and marine applications.
- Distinctive red colour for easy identification.
- Good low temperature properties.
- Ideal for hydraulic systems especially those exposed to wide temperature variations.

PERFORMANCE PROFILE:

Millermatic Type UN meets the requirements of:

- General Motors Dexron IID Ford Mercon M2C 138J,M2C 166H,M2C 185A,
- MAN 339 Type Z1,Type V2 Voith V55,6335
- Caterpillar TO-2 Renk
- Sperry-Vickers Hydraulic Allison C4
- Hagglunds Denison HF-O Sundstrand Systems
- MB 236.1, 236.5, 236.6, 236.7 ZF TE-ML-O2F,O4D,O9,11A,11B,14A,17C

TYPICAL CHARACTERISTICS:

Specific Gravity @ 15°C	0.866
Kinematic Viscosity @ 100°C	7.5cSt
Kinematic Viscosity @ 40°C	38.9cSt
Viscosity Index	164
Pour Point °C	-42
Flashpoint °C	210
Colour	Red

HEALTH AND SAFETY:

Health and Safety Data Sheet 5386 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

Millers Oils Limited
Brighouse
West Yorkshire
HD6 3DP

Tel +44 (0)1484 713201
Fax +44 (0)1484 721263
Email enquiries@millersoils.co.uk
www.millersoils.co.uk

