



millersoils.co.uk

PRODUCT DATA SHEET



AUTOMOTIVE



DATA SHEET NO: 5339

PRODUCT NAME/VISCOSITIES:

CLASSIC GEAR OIL EP 140 GL4

DESCRIPTION:

High performance solvent refined mineral base oil treated with performance additives.

APPLICATION:

Use as received in classic gearboxes and differentials requiring extreme pressure (EP) lubricants and GL4 specification.

USER BENEFITS:

- Provides performance level specified by manufacturers for gearboxes and axles.
- Viscosity selected to meet classic vehicle requirements.
- Low friction and reduced noise.

PERFORMANCE PROFILE:

- API GL-4
- MIL-L-2105

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	140
Specific Gravity @ 15°C	0.905
Kinematic Viscosity @ 100°C	31.0cSt
Kinematic Viscosity @ 40°C	484.3cSt
Viscosity Index	94
Pour Point °C	-9
Flashpoint °C	238

HEALTH AND SAFETY:

Health and Safety Data Sheet 5339 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

Millers Oils Limited
Brighouse
West Yorkshire
HD6 3DP

Tel +44 (0)1484 713201
Fax +44 (0)1484 721263
Email enquiries@millersoils.co.uk
www.millersoils.co.uk

