



DATA SHEET NO: 5217

## PRODUCT NAME/VISCOSITIES:

# CLASSIC DIFFERENTIAL OIL EP 90 GL5

#### **DESCRIPTION:**

High quality solvent refined base stocks with performance additives.

#### APPLICATION:

Use as received in Hypoid differentials requiring extreme pressure lubricants and GL5 specification. For highly loaded hypoid transmissions. Also suitable in transmissions with brass & bronze components.

#### **USER BENEFITS:**

- Well proven superior performance.
- Provides 'trouble free' operation.
- Imparts exceptional load carrying ability.
- Friction modified for mild limited-slip applications.

#### PERFORMANCE PROFILE:

Provides performance meeting or exceeding:

- API GL5
- MIL-L-2105D
- OEM performance levels for final drives.

### TYPICAL CHARACTERISTICS:

SAE Viscosity Grade 90
Specific Gravity @ 15°C 0.893
Kinematic Viscosity @ 100°C 15.4cSt
Kinematic Viscosity @ 40°C 153.0cSt
Viscosity Index 102
Pour Point °C -18
Flashpoint °C 205

## **HEALTH AND SAFETY:**

Health and Safety Data Sheet 5217 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

Millers Oils Limited Brighouse West Yorkshire HD6 3DP Tel +44 (0)1484 713201 Fax +44 (0)1484 721263 Email enquiries@millersoils.co.uk www.millersoils.co.uk











For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

Millers Oils Limited Brighouse West Yorkshire HD6 3DP

Tel +44 (0)1484 713201 Fax +44 (0)1484 721263 Email enquiries@millersoils.co.uk www.millersoils.co.uk





