

AUTOMOTUS WITHER SOITS

DATA SHEET NO: 5110

PRODUCT NAME/VISCOSITIES:

CLASSIC GREEN GEAR OIL 250 GL1

DESCRIPTION:

High viscosity solvent refined mineral oil.

APPLICATION:

Use as received for lubrication of transmission systems which preclude the use of extreme pressure (EP) types.

USER BENEFITS:

- Non EP formulation [GL1] specifically for vintage applications.
- Contains inhibitors to prevent formation of rust.
- Good oxidation resistance and long life.

PERFORMANCE PROFILE:

API GL-1

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade 250
Specific Gravity @ 15°C 0.928
Kinematic Viscosity @ 100°C 71.4cSt
Kinematic Viscosity @ 40°C 1048cSt
Viscosity Index 136
Pour Point °C -6
Flashpoint °C 200

ISO Viscosity Grade 1000

HEALTH AND SAFETY:

Health and Safety Data Sheet 5110 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

Millers Oils Limited Brighouse West Yorkshire HD6 3DP Tel +44 (0)1484 713201 Fax +44 (0)1484 721263 Email enquiries@millersoils.co.uk www.millersoils.co.uk





